



## RAX500 & CCU II Automatic cable reel up to 500m with CCU II

Automatic cable reel for the ROVION inspection system. The cable reel holds max 500 m of armored camera cable and offers winding support. The winding speed and the pulling force is infinitely variable. The control unit CCU II serves as power supply and video processing of the RAX500.

- Max. 500 m extremely robust camera cable
- Meter counter
- Integrated adjustable deflection pulley
- Continuous brake
- Vertical/horizontal operation
- Radio remote control
- Winding support



## Technical data - RAX500

Drive	Motor-driven
Cable length	max. 500 m
Meter counter	1
Integrated deflection pulley	Yes
Large deflection pulley	Yes
Voltage	230 V AC/115 V AC
Frequency	50 Hz/60 Hz
Electrical current	2.5 A/5 A
Fuses	6.3 A (delay fuse)
Protection class	IPX4
Ambient temperature range	0°C to 40°C
Storage temperature range	-20°C to 70°C
Dimensions (WxHxD)	520 x 674 x 680 mm
Weight (incl. cable)	approx. 111 kg

## Technical data - Control unit CCU II

Special equipment	Video processing
Interfaces (rear)	1 x Sub-D 25 poles (CCU1), 1 x M16 Hummel connector (automatic cable reel), 1 x Sub-D 5 poles (SAT-cable reel), 1 x IEC connector (power supply plug)
Voltage	230 V AC/115 V AC
Frequency	50 Hz/60 Hz
Electrical current	2 A/4 A
Input power	Max. 460 W
Protection class	IP20 (protect from humidity and moisture, not suitable for outdoors)
Material (front plate)	Aluminum
Dimensions (WxHxD)	483 x 88.9 x 417 mm
Rack	19", 2 HU
Weight	approx 6 kg



**IPEK International GmbH** · See, Gewerbepark 22 · 87477 Sulzberg · GERMANY  
☎ +49 8376 921 800 📠 +49 8376 921 8021 ✉ [isg\\_info@idexcorp.com](mailto:isg_info@idexcorp.com) 🌐 [www.ipel.com](http://www.ipel.com)

Issue: February 2018 - subject to changes - ROVION, AGILIOS, XPECTION are registered trademarks of IPEK

